

# GT902



Standard Wheel  
  Permitted Wheel  
  Prohibited Wheel

- Suitable for tractors trailers.
- All positions, fit for driving on various roads.
- Mature pattern design, superior traction performance, braking performance and wet sliding resistance.
- High efficiency of heat dissipation and strong driving force due to large tread groove on shoulder.



TYRE SIZE	PLY RATING	TREAD DEPTH (MM)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER(mm)	SECTION WIDTH (mm)	INFLATION PRESSURE (kpa)		LOAD CAPACITY (kg)	
									SINGLE	DUAL	SINGLE	DUAL
9.00R20	16PR	15.50	7.00	TT	144/142	L	1019	259	900	900	2800	2650
10.00R20	18PR	16.50	7.50	TT	146/143	L	1054	278	830	830	3000	2725
11.00R20	18PR	17.00	8.00	TT	152/149	L	1085	293	930	930	3550	3250
12.00R20	20PR	16.00	8.50	TT	156/153	L	1125	315	900	900	4000	3650
12.00R24	20PR	14.50	8.50	TT	160/157	K	1226	315	900	900	4500	4125
11R22.5	16PR	14.50	8.25	TL	146/143	M	1054	279	830	830	3000	2725
12R22.5	18PR	15.00	9.00	TL	152/149	M	1085	300	930	930	3550	3250
13R22.5	18PR	16.00	9.75	TL	154/151	M	1124	320	830	830	3750	3450
315/80R22.5	20PR	15.00	9.00	TL	156/150	M	1076	312	850	850	4000	3350